

Miscellaneous Insulating, Ceramic, Metallic and Conducting Materials - Component

COMPANY

AOCHUAN TECHNOLOGY(HEYUAN) CO.,LTD
The fourth floor of the plant C of Wiley Printing(Heyuan) CO.,LTD,Nation-Tech Deveiopment Zone
Heyuan, Guangdong Sheng 517001 China

E525137

Mtl		Min	Overall	Metal											
Dsg	Color	Thk (mm)	Thk (mm)	Thk (mm)	No. Conductors	No. Layers	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	GWIT	GWFI	CTI
Addition cured, Pt catalyze, Silicone, fiberglass composite furnished as roll or sheets															
TC3000(#)	WT, BL	0.16-0.55	-	-	-	3	V-0	-	-	150	150	150	-	-	-
Addition cured, Pt catalyze, Silicone, fiberglass composite composite furnished as sheets															
UTP100	RD, GY	0.5	-	-	-	3	V-0	-	-	150	150	150	-	-	-
		3.0	-	-	-	3	V-0	-	-	150	150	150	-	-	-
Addition cured, Pt catalyze, Silicone, Polyimide film composite furnished as rolls or pieces															
TCK10	BG, GY	0.15-0.165	-	-	-	3	V-0	-	-	130	130	130	-	-	-
Addition cured, Pt catalyze, Silicone, Polyimide film composite furnished as sheets															
TCK15B(#)	GY, RD	0.2-0.22	-	-	-	3	V-0	-	-	130	130	130	-	-	-

Mtl		Min												
Dsg	Color	Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	GWIT	GWFI	CTI			
Addition cured, Pt catalyze, Silicone, fiberglass composite furnished as rolls or pieces														
TC1500	GN, YL	0.25-0.275	V-0	4	0	150	150	150	-	-	0			
TC2000	NC, RD	0.25	V-0	-	-	150	150	150	-	-	-			
		0.50-0.55	V-0	-	-	150	150	150	-	-	-			
TC900S	PK, BL	0.23-0.253	V-0	-	-	150	150	150	-	-	-			

(#) - IEC 60112 CTI: 600V, Material Group: I.

Marking: Company name, material designation on container, wrapper or finished part.

Last Updated on 2023-05-06

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过 UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明： "©2023 UL LLC."

Feedback