

QMFZ2.E524248 - Plastics - Component

Plastics - Component

AOCHUAN TECHNOLOGY(HEYUAN) CO.,LTD

The fourth floor of the plant C of Wiley Printing(Heyuan) CO.,LTD,Nation-Tech Deveipment Zone

Heyuan, Guangdong 517001 China

E524248

Dsg	Color	Min		H	H		RTI		H	D	
		Thk	Flame	W	A	Elec		Mech	T	9	C
		mm	Class	I	I	Str	Imp	Str	R	5	I
Silicone "Room Temperature Vulcanizing" (RTV),addition-cure, vinyl, platinum catalyzed furnished as sheets											
TP(Y)	ALL	0.5	V-0	2	0	150	150	150	-	-	0
		3.0	V-0	1	0	150	150	150	-	-	-
Silicone "Room Temperature Vulcanizing" (RTV),addition-cure, vinyl, platinum catalyzed furnished as two liquid components											
GF(X)	GY, BL	0.5	V-0	-	-	150	150	150	-	-	-
		3.0	V-0	-	-	150	150	150	-	-	-
TF(Y)	ALL	0.5	V-0	2	0	150	150	150	-	-	0
		3.0	V-0	1	0	150	150	150	-	-	-

(X) - Replaced by digits from 100 to 600 to represent aluminum oxide content

(Y) - Replaced by digits from 080 to 1500 to represent aluminum oxide content

Marking: Company name, material designation On container, wrapper Or finished part.

Last Updated on 2022-08-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Feedback